

ET407 Webpad System Pictures and Specification:



ET407 Webpad Specifications

Mobile Windows-Based Terminal

- Based on Windows CE .NET operating system
- Integrated Microsoft RDP and Citrix ICA protocols
- ROM: 32Mb FLASH (Expand to 64MB)
- RAM: 64Mb SDRAM (Expand to 128MB)

Display Support

- 8.4" TFT LCD 800x600 touchscreen panel
- VRAM: 1280KB
- Color: 64K colors

Audio

- Stereo speakers
- Microphone
- Audio in: 1/8" mini, line in 8 bit
- Audio out: 1/8" mini, full 16 bit, 48 khz sampling rate
- External jack for headphone

Input/Output/Peripheral Support

- 1 Type II PCMCIA slot
- 1 Type II CF slot
- 1 SD/MMC slot
- 1 IrDA port
- 2 USB Host port
- 1 USB Client port
- 1 Stereo earphone jack
- 1 Microphone jack
- 1 CRT/RS-232 port

Operating System and Software

- Microsoft CE .NET
- Internet Explorer 6
- Windows Media Player 9
- WordPad
- Windows Messenger
- Inbox
- Microsoft Office Viewer: Word, Excel, PDF, Powerpoint, Image

- RDP 5, ICA 6
- Personal information manage: Name card, schedule category, Memo, sketch, anniversary, alarm, painter, world clock, expense, calculator
- Games: Solitaire, FreeCell

Utility Program

- Setup Tool: Power, Button, Connection, Backlight
- Quick Launch
- Input Method Selector
- 802.11b Wireless Setup Tool
- Transcriber Handwriting Recognizer Application
- Flash Update Tool
- Backup Tool: Registry, File, Object Store Database

Set-Up and Configuration

User Interface

- Traditional Microsoft Windows Shell Interface
- Local boot
- International software keyboard: English, Japanese, Simplified Chinese, Traditional Chinese, and more

Physical Characteristics

- Height: 8.8 inches (224 mm)
- Width: 6.7 inches (170 mm)
- Depth: 0.9 inches (21.7 mm)
- Shipping weight: 1.8 lbs (800g)

Environmental

Temperature range

- Powered on: 50° to 104°F (10° to 40°C)
- Powered off: -40° to 140°F (-40° to 60°C)
- Convection cooling, fanless design

Humidity

- 20% to 80% noncondensing
- 0 to 10,000 feet (0 to 3,050 meters)

Power

- Worldwide auto-sensing 100-240v VAC, 50/60 Hz
- AC Adapter
- Li-Ion Battery (up to 6 Hours between charges)
- Integrated Battery & Charger 100-240 VAC, 50-60 Hz

Regulatory Compliance

Safety

- UL/CUL(UL60950;CSA-C22.2 NO.60950-00)
- CB (IEC60950)

RF interference

- FCC Class B
- CE mark
- VCCI
- BSMI

Accessories

- Extended operation battery (up to 6 hours between charges)
- Nylon carrying case
- AC adapter
- Stylus
- USB transmission line
- For more available accessories, please visit www.ewayco.com

Warranty

- One-year limited hardware warranty

e-Way ET407 Webpad

This information subject to change from time to time without notice, actual item may vary.

Copyright 2004 e-Way and others, Copyrights and trademarks owned by respective owners.