









PPC-1510PT 15" Panel PC with Low Power 800Mhz CPU with VGA / LAN / Audio / 4xCOM / 2xUSB

 <p>Ultra thick solid Aluminum Alloy IP-65, NEMA 4, VESA-75, 100</p>	 <p>Cable-Less Design for best Vibration & Shock resistant</p>	 <p>Tapped screw holes, VESA 75 and 100,</p>	 <p>fill water into panel until full</p>
 <p>USB, LAN, Audio, 4xCOM, Printer, KB, Mouse, 2xPCI</p>	 <p>Screw mount</p>	 <p>Quick wall-mounted Kit</p>	 <p>100% Water-Resistant Test on front panel for 7 days</p>

15.1" TFT Panel PC with Touch / LAN / 4 x COM / 2 x USB / PCMCIA / CF / Audio / CDROM

LCD Display

15" color TFT LCD, 1024 x 768 high resolution
250 cd/m² high brightness

CPU - Low Power 800Mhz

P-III equivalent Low power 800Mhz CPU
soldered on board, (Low Power 1Ghz is optional)

System Chipset

VIA VT8601 Northbridge and VIA686B

System Memory : (Optional)

Support up to 512MB SDRAM memory

Touch Panel :

Long life 5-Wire Resistive touch screen optional

Front Bezel

Thick 10mm solid Aluminum-alloy, with highest
level surface treatment

Housing & Wall-mounting

Rugged 1.2mm thick steel metal sheet with
white painting

VESA -75 and VESA-100 compliant

Water-Resistant on Front Panel

Meet IP-56, 65, NAMA 4, 12 water resistant

Surface Treatment of Front Panel

Super high-end polish, sand-blast, hairline
anodizing treatment. Standard color is Stainless
Steel silver Color or Black

CD-ROM : One CD-ROM, 24x speed

HDD : (Optional) 20 or 30GB HDD

10, 20, or 30GB slim size HDD is (Optional)

Disk On Module - optional

Support DOM up to 512MB (optional)

Serial ports : 4 x COM ports

(3 x RS232 ports and 1 x RS232/422/485)

1 x COM was assigned for touch screen

USB port : 2 x USB ports

Quick wall-mount Kit – special design

Nagasaki Special design quick wall-mount kit

PCI Slot : 2 x PCI expansion slots

Parallel Port : LPT port for Printer connection.

Keyboard and Mouse : One PS/2 KB Mouse

Audio – built in high quality speakers

Built in high quality speakers, Microphone jack,
Line-in jack

Ethernet Network Controller

Realtek 8139C, support 10/100 Mbp, auto-
negotiation, auto-switch LAN

VGA - Display Controller Chipset

Trident chipset support AGP 4X LCD/CRT with
8MB share Video memory, 3D/2D support
DVD MPEG-2 : support DVD video playback

Vibration-Resistant Design

Excellent cable-less design for vibration and
shock resistant ability,
5 - 17 Hz, 0.1" double amplitude displacement,
17-500 Hz, 1.5G acceleration peak to peak

Shock-Resistant Design

10G acceleration peak to peak (11 msec.
duration)

Power Supply : AC-DC or DC-DC optional
External power supply UL/CE safety approved

Dimension (WxHxD)

Please call our sales

Operating Temperature :

0 to 55°C (32 to 131°F)

Ordering information :

PPC-1510P : without Touch

PPC-1510PT : with Touch screen